

ACT 10

Product Overview

The ACT 10 digital keypad is a sturdy and durable unit made from vandal resistant die cast zinc with backlit stainless steel keys. This multi-purpose keypad caters for access control, door monitoring and interlock applications.

Main Features

- 10 User codes
- 2 Output relays
- 2 doors, 2 user groups
- Interlock, fire alarm input, door monitoring
- Surface or Flush mount options
- Indoor or outdoor (IP54)
- Zinc diecast housing, stainless steel keys
- Front and back tamper
- Backlit keypad

Installation / Specification Guidelines

- The ACT 10 requires an operating voltage of 12 to 24 volts AC or DC. For full functionality use 12 volts DC supply.
- 2 x 5 amp relay outputs
- The ACT 10 can be installed either indoors or outdoors (IP54)
- Operating Temperature: -10 to +50 C
- There are flush mounting and weather shield accessories available for this product


Digital Keypad

ACT

Access Control Technology



ACT 10



ACT 10 System Schematic

ACT 10

Product Specification

Operating Voltage: 12/24 Volts AC/DC
 Current Consumption: 40/120 mA
 Weight: 700 grams
 Operating Temperature: -10 to +50 C
 Dimensions (HxWxD): 138 x 87 x 37 mm
 Mounting: Surface or Flush
 Installation: Indoor or Outdoor

Digital Keypad



Access Control Technology



ACT 10 Digital Keypad

ACT 10 Flush Kit

Product Specification

Front Plate Dimensions (HxWxD):	185 x 130 x 3 mm
Back Box Dimensions (HxWxD):	150 x 90 x 40 mm
Weight:	750 grams

ACT 10 Weather Shield

Product Specification

Dimensions (HxWxD):	140 x 92 x 74 mm
Weight:	475 grams

ACT Standalone products comparison chart

Feature	ACT 5	ACT 10	ACTsmart2 1070	ACTsmart2 1080	ACTsmart2 1090
Doors	1	2	1	1	1
Users	10	10	1000	1000	1000
User groups		2	1	1	1
Proximity			Yes	Yes	
Pin & Proximity				Yes	
Pin Only	Yes	Yes		Yes	Yes
Door Monitor		Yes	Yes	Yes	Yes
Fire Override		Yes	Yes	Yes	Yes
Interlock		Yes	Yes	Yes	Yes
Five amp Lock Output	Yes	Yes	Yes	Yes	Yes
Door release Input	Yes	Yes	Yes	Yes	Yes
Auxiliary Input		2	1	1	1
Auxiliary Output		2			
Auxiliary I/O			2	2	2
Duress Code		Yes	Yes	Yes	Yes
Tamper		Yes	Yes	Yes	Yes
Backlighting		Yes			
Master/Slave			Yes	Yes	Yes
Flush Mount option	Yes	Yes	Yes	Yes	Yes
Indoor/Outdoor	IP67	IP54	IP67	IP67	IP67
Toggle Mode		Yes	Yes	Yes	Yes



ACT 10 Flush Kit



ACT 10 Weather Shield

